


J45416



1- The 125mm diameter posts are made of painted galvanised steel. The grained finish has a slightly undulating surface for increased scratch resistance.




**2- The caps** are made of rotary moulded polyethylene (A) or injection moulded polyamide (B).



3- The platforms are made from a 12.5mm thick, textured, non-slip compact material (HPL).

Further reinforcement is provided by lacquered galvanised steel supports, located on the underside of the platforms.



4- The play walls and roofs are made from a 13mm thick compact material (HPL). Robust in construction, it has excellent weather and vandal resistance properties.



5- Stainless steel version: the play walls bring together a coloured panel and a stainless steel sheet, 1.5mm thick with a patterned surface on both sides to make it scratch-proof. The roofs are made of polyethylene 10mm thick.



6- Aluminium version: the play walls and roofs are made of painted aluminium sheet 3mm thick, backed with a coloured panel.

Proludic



7- The 16mm diameter rope is made of galvanised steel cable covered with polyester. The net fittings are made of polyamide and used to link three cords together.



8- The tubes are made of 40mm diameter stainless steel, guaranteeing lasting durability and reliability of the equipment.



**9- Injection moulded polyamide fixings** connect the posts with the platforms and the various play features. They are non-toxic, flameproof and U.V. resistant. The thickness of the polyamide makes the equipment both strong and vandal resistant.



**10-The steps** are made of shock-absorbing rubber with non-slip surfaces.



**11-The sliding surface** is made of 2mm thick stainless steel, which is shaped, bent and rolled from one piece.



**12-The tunnel** is made of 100% recycled rotomolded polyethylene, 76cm in diameter (RAL 9005).



**13-The fixings** are made of stainless or plated steel and protected by anti-vandalism polyamide caps.

Proludic