

Aquatica (technical specification)

J1961



1- The 125mm diameter posts are made of painted galvanised steel. The two-tone grey grained finish has a slightly undulating surface for increased scratch resistance. The caps are made of injection moulded polyamide.



2- The 95 x 95mm posts are made of painted galvanised steel, ensuring robustness and durability. The caps are made of injection moulded polyamide.



3- The platforms are made from a 12.5mm thick, textured, non-slip compact material (HPL).

Further reinforcement is provided by galvanised steel supports, located on the underside of the platforms.



4- The coloured panels are made from a 13mm thick compact material (HPL). Robust in construction, it has excellent weather and vandal resistance properties.



5- The tubes are made of 40mm diameter stainless steel, guaranteeing lasting durability and reliability of the equipment.



6- Injection moulded polyamide fixings connect the posts with the platforms and the various play features. They are non-toxic, flameproof and U.V. resistant. The thickness of the polyamide makes the equipment both strong and vandal resistant.





7- The 16mm diameter ropes are made of galvanised steel cable covered with polyester. The cables are linked together and held in place by injected polyamide spheres.



8- The sliding surfaces are made of 2mm thick stainless steel, which is shaped, bent and rolled from one piece.



9- The tunnel is made of 100% recycled rotomolded polyethylene, 45cm in diameter (RAL 9005).



10-The one-piece rail is made of stainless steel, \emptyset 76.1mm, 3.6mm thick. The trolley is made of stainless steel ensuring its durability.



11-The grip section of the stainless steel handle is overmoulded with rubber to give a good grip.



12-The climbing holds are made of polyamide for its strength and rigidity.



13-The fixings are made of stainless or plated steel and protected by anti-vandalism polyamide caps.

