



1- The 95 x 95mm posts are made of painted galvanised steel, ensuring robustness and durability.



2- The 125mm diameter posts are made of painted galvanised steel, ensuring robustness and durability. The caps are made of injection moulded polyamide.



3- The junction pieces are made of painted galvanised steel.



4- The coloured panels are made from a 13mm thick compact material (HPL). Robust in construction, it has excellent weather and vandal resistance properties.



**5-** The platforms are made from a 12.5mm thick textured and non-slip compact material (HPL).



6- The tubes are made of 40mm diameter stainless steel, guaranteeing lasting durability and reliability of the equipment.

Proludic



7- Injection moulded polyamide fixings connect the posts with the platforms and the various play features. They are non-toxic, flameproof and U.V. resistant. The thickness of the polyamide makes the equipment both strong and vandal resistant.



8- The sliding surface is made of 2mm thick stainless steel, which is shaped, bent and rolled from one piece.



**9- The 16mm diameter ropes** are made of galvanised steel cable covered with polyester. The cables are linked together and held in place by injected polyamide spheres.



10-The net fittings are made of polyamide and are used to link three cords together.



11-The steps are made with a non-slip rubber overmould.



12-The caps are made of rotary moulded polyethylene.



13-The climbing holds are made of polyamide for its strength and rigidity.





14-Plastic parts are made of injected polyamide.



**15-The fixings** are made of stainless or plated steel and protected by anti-vandalism polyamide caps.

