

Climbing equipment

(technical specification)

J57012



1- The 95 x 95mm posts are made of painted galvanised steel, ensuring robustness and durability.



2- The 125mm diameter posts are made of painted galvanised steel. The two-tone grey grained finish has a slightly undulating surface for increased scratch resistance. The caps are made of injection moulded polyamide.



3- The junction pieces are made of painted galvanised steel.



4- The coloured panels are made from a 13mm thick compact material (HPL). Robust in construction, it has excellent weather and vandal resistance properties.



5- The platforms are made from a 12.5mm thick textured and non-slip compact material (HPL).



6- The tubes are made of 40mm diameter stainless steel, guaranteeing lasting durability and reliability of the equipment.





7- Injection moulded polyamide fixings connect the posts with the platforms and the various play features. They are non-toxic, flameproof and U.V. resistant. The thickness of the polyamide makes the equipment both strong and vandal resistant.



8- The 16mm diameter ropes are made of galvanised steel cable covered with polyester. The cables are linked together and held in place by injected polyamide spheres.



9- The net fittings are made of polyamide and are used to link three cords together.



10-The steps are made with a non-slip rubber overmould.



11-The sliding surface is made of 2mm thick stainless steel, which is shaped, bent and rolled from one piece.



12-The Kayak slide is made of rotomoulded polyethylene.



13-The caps are made of rotary moulded polyethylene.





14-The climbing holds are made of polyamide for its strength and rigidity.



15-The fixings are made of stainless or plated steel and protected by anti-vandalism polyamide caps.

